

SERVER STATION

32 Channel Connected Cameras


VIEWNET 3500 PLUS



Key Features

- 32 Channel connected cameras
- Central management system
- Supports GPU hardware decoding to save CPU resources
- Windows Embedded System 7
- Storage 4 HDDs connectable
- Third-party product integration via ONVIF
- Decoding performance 2*4K / 9 * 1080p

Rear Panel



Technical Specifications

Server Station	VIEWNET 3500 PLUS
Management mode	Central management system
Connected	Number of connected cameras : 32 Maximum number of connected clients : 10 Maximum number of cascading station : 15
Number of users	32
Decoding performance	2 * 4K / 9 * 1080p
Incoming bandwidth	32 * 4 Mbps
Outgoing bandwidth	16 * 4 Mbps
Support	C/S client, Web Client, Mobile Client, Stream Media Server, Third-party cameras, Alarm management Map, Two-way audio, Broadcast, PTZ control, Fisheye expansion, People counting report
Integration	Third-party product integration via ONVIF
Standard screen layout	1, 4, 6, 8, 9, 13, 16, 25, 32, 36, 64
Wide screen layout	4, 6, 7, 9, 12, 16, 24, 36, 48
Auxiliary screen	1(main)+3(auxiliary) screens supported
Instant playback	Instant playback in live-view screen
Operation panel	Manual record / Snapshot / PTZ / E-Zoom Audio supported
Display layout	Up to 16-channel simultaneous playback
Search mode	Camera , Time , Event , VCA playback search
Speed control	1/8x, 1/4x, 1/2x, 1x, 2x, 4x, 8x supported
Alarm log	Alarm log , Operation log , System log , Device log
Backup	Log back-up as .csv
Operating system	Windows Embedded System 7
Storage	4 HDDs connectable, up to 24 TB
Memory	4 GB
mSATA support	Yes (32 GB)
Video output	1 HDMI output, 1 VGA output
Network interface	2 10M/100M/1000M self-adaptive Ethernet interfaces
USB interface	4 x USB 2.0, 1 x USB 3.0
Alarm in/out	4/2
Audio in/out	1/1
Consumption	≤30 W
Working temperature	0°C ~ +45°C
Working humidity	10% to 90%
Chassis	19" 1.5U
Dimensions	440 mm × 400 mm × 66 mm
Weight	7.6 kg (16.8 lb)