

## IP CAMERA

### 2MP & 1.3MP CMOS Alarm Pro Cube Camera

VNC-1291W / VNC-1190W .....


Technical Specifications .....



## Key Features .....

- 1/2.8" progressive scan CMOS
- 1920 x 1080 @ 25fps frame rate
- 4.0mm fixed lens
- H.264 / MJPEG Compression
- Up to 10m IR distance
- Build-in microphone and speaker
- Support two-way audio
- Support PIR (Passive Infrared Detection)
- Support Line crossing and intrusion detection
- DWDR, 3D DNR, ROI, Defog
- W Series : Built-in Wi-Fi
- PoE, ONVIF

## Dimensions .....



UNIT:mm

Model NO.	VNC-1291W	VNC-1190W
Image Sensor	1/2.8" Progressive Scan CMOS	
Min. Illumination	0.01Lux @(F1.2) / 0.028Lux @(F2)	
Lens	4mm@ F2.0, Angle of view: 85°	
Day & Night	IR cut filter with auto switch	
Digital Noise Reduction	3D DNR	
Wide Dynamic Range	Digital WDR	
Video Compression	H.264 / MJPEG	
Video Bit rate	32 Kbps ~ 8 Mbps	
Audio Compression	G.711/G.722.1/G.726/MP2L2	
Audio Bit Rate	64Kbps(G.711) /16Kbps(G.722.1)/16Kbps(G.726)	
Max. Resolution	1920 x 1080	1280 x 960
Frame Rate	50Hz: 25fps(1920 x 1080), 25fps (1280 x 960), 25fps (1280 x 720) 60Hz: 30fps(1920 x 1080), 30fps (1280 x 960), 30fps (1280 x 720)	
Image settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser	
Features	BLC, ROI, Defog	
Local storage	Micro SD/SDHC/SDXC card slot, up to 64 GB	
Network storage	NAS (Support NFS,SMB/CIFS)	
Alarm trigger	Intrusion detection, Line crossing detection Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS DDNS, RTP, RTSP, RTCP, PPPoE,NTP,UPnP,SMTP SNMP, IGMP, 802.IX, QoS, IPv6, Bonjour	
General	One-key reset, Flash-prevention, dual stream heartbeat,mirror,password protection,privacy mask watermark,IP address filtering,Anonymous access	
System compatibility	ONVIF, PSIA, CGI, ISAPI	
Communication interface	1 RJ45 10M / 100M ethernet port	
Alarm input/output	1/1	
Wireless Standards	IEEE802.11b, 802.11g, 802.11n	
Frequency Range	2.4 GHz ~ 2.4835 Ghz	
Channel Bandwidth	20/40MHz Support	
WIFI Protocols	802.11b: CCK, QPSK, BPSK / 802.11g/n: OFDM	
WIFI Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	
Wireless Range	50m(depend on environment)	
Operating conditions	-30°C ~ +60°C , Humidity 95%	
Power supply	DC12V/PoE(802.3af)	
Power consumption	5.5W MAX	
IR range	10 meters	
Dimensions	72.3×89.9×131.3	
Weight	400g(0.88lbs)	