

PTZ IP CAMERA

2MP Network IR PTZ Dome Camera



VNC-2281



Key Features

- 1/2.8" Progressive Scan CMOS
- 1080P Full HD resolution
- 20X Optical Zoom
- DWDR
- 3D intelligent positioning function
- Up to 150m IR distance
- Hi-PoE / 24VAC power supply
- Support BNC output

Dimensions



Unit:mm

Technical Specifications

Model No	VNC-2281
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	F1.5, AGC On: Color: 0.02 lux, B/W : 0.002 lux
Features	Privacy Mask, Digital Zoom 16x, HLC, BLC, DWDR 3D DNR, IR Cut Filter, Dual Streams
Focal Length	4.7 ~ 94mm, 20x
Angle of View	58.3 ~ 3.2 degree (Wide-Tele)
Pan/Tilt Range	Pan: 360° endless; Tilt: -15° ~ 90° (Auto Flip)
Pan/Tilt Speed	Pan:Manual :0.1°~400°/s,Preset Speed:400°/s Tilt:Manual :0.1°~200°/s,Preset Speed:200°/s
Number of Preset	300
Park Action	Pattern/Pan scan/Tilt scan/Frame scan Panorama scan/Random scan
Patrol	8 patrols, up to 32 presets per patrol
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan Random scan / Frame scan / Panorama scan
IR Distance	Up to 150m
IR Intensity	Automatically adjusted,depending on zoom ratio
Alarm I/O - Trigger	2/I - Intrusion detection, Line crossing detection Audio exception detection, Motion detection
Alarm Action	Preset, Patrol, Pattern, Recording, Relay output Upload center, Upload FTP, Email linkage
Audio input	1 Mic in/Line in interface
Audio output	1Audio output interface,Line level,impedance:600Ω
Ethernet	10Base-T / 100Base-TX, RJ45 connector
Max. image resolution	1920x1080
Frame Rate	50Hz: 25 fps (1920x1080), 25 fps (1280x960) 25 fps (1280x720) 60Hz: 30 fps (1920x1080) 30 fps (1280x960) , 30 fps (1280x720)
Image Compression	H.264/MJPEG
Audio Compression	G.711u /G.711a /G.726 /MP2L2
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP,TCP UDP, IGMP, ICMP, DHCP, PPPoE
Simultaneous Live View	Up to 20 users
Mini SD Memory Card	Micro SD slot, up to 32GB
User/Host Level	Up to 32 , 3 Levels: Administrator, Operator, User
Application programming	Open-ended API, support Onvif, PSIA and CGI
Web Browser	IE 7+, Chrome 18+, Firefox 5.0+, Safari 5.02+
Power	High-PoE&24 VAC, Max30W
Working temperature	-30°C ~ +65°C , Humidity 90%
Protection Level	IP66, TVS 4,000V lightning protection, surge protection and voltage transient protection
Dimensions	Φ266.6(mm)×365.2(mm)
Weight	4kg (8.8lbs)