

## SMART IP CAMERA

### 5 MP Network Turret Camera


#### VNC-5565



#### Key Features

- 1/2.9" progressive scan CMOS
- 2560 × 1920 @20fps frame rate
- 2.8mm, 4mm, 6mm, 8mm, 12mm, Fixed lens
- True WDR, up to 120dB
- H.265+, H.265, H.264+, H.264 Compression
- EXIR technology, up to 30m IR distance
- Support Full Smart Function
- 3D DNR, ROI, EIS, Defog
- PoE, ONVIF, SD Card
- S Series : Audio I/O, Alarm I/O ( Optional )
- IP67 weatherproof

#### Dimensions



#### Technical Specifications

Model No	VNC-5565
Image Sensor	1/2.9" progressive scan CMOS
Min. Illumination	Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR
Shutter Time	1/3 s to 1/100,000 s
Slow Shutter	Support
Lens	2.8mm, 4mm, 6mm, 8mm, 12mm, Fixed lens
Lens Mount	M 12
Iris	F 2.0
Day & Night	IR cut filter
Digital Noise Reduction	3D DNR
Wide Dynamic Range	120dB WDR
Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.265+	Support
Video bit rate	32 Kbps ~ 16 Mbps
Max. resolution	2560 × 1920
Frame rate	50Hz: 20 fps (2560 × 1920), 25 fps (2560 × 1440), 2048 × 1536, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (2560 × 1920), 30 fps (2560 × 1440), 2048 × 1536, 1920 × 1080, 1280 × 720)
Image Enhancement	Defog, BLC, EIS, ROI
Image settings	Support rotate mode. Brightness, contrast, saturation and sharpness are adjustable via web browser
Network Storage	Support microSD/SDHC/SDXC card (128G) local storage, NAS (NFS, SMB/CIFS), ANR
Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnected, IP Address Conflict, HDD full, error
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General Function	One-key Reset, Anti-Flicker, Heartbeat, Mirror Password Protection, Privacy Mask, Watermark
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
On-board Storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Smart Features	Behavior Analysis, Line Crossing Detection, Intrusion Detection, Object Removal Detection, Unattended Baggage Detection, Face Detection
Operating Conditions	-30 °C to +60 °C (-22 °F to +140 °F), Humidity 95%
Power Supply	12 VDC ± 25%, 6.5 W , PoE( 802.3af ), 8.5 W
IR Range	Up to 30 m
Protection Level	IP 67
Dimensions	Φ 127.3 × 95.9 mm (5.01" × 3.78")
Weight	620 g (1.37 lb.)