

SPECIAL IP CAMERA

2 MP Anti-Corrosion Network IR Dome Camera

VNC-6270



Technical Specifications

Model No	VNC-6270
Image Sensor	1/1.8" Progressive Scan CMOS
Min. Illumination	0.002 Lux (@ F1.2, AGC ON) 0 Lux with IR
Shutter Speed	1 s to 1/100,000 s
Slow Shutter	Support
Lens	2.8-12mm F1.4, angle of view: 92°-32°
Lens Mount	Φ14
Adjustment Range	Pan: 0°-355°, tilt: 0°-75°, rotation: 0°-355°
Auto Iris	DC Drive
Day & Night	IR cut filter with auto switch
WDR	120 dB
Video Compression	H.264 / MJPEG / MPEG4
H.264 encoding level	Base Line Profile/ Main Profile/ High Profile
Video Bit rate	32Kbps-16Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Bit rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726)
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 50fps (1920x1080,1280x960,1280x720); 60Hz: 60fps (1920x1080,1280x960,1280x720)
Image Settings	Corridor mode, Saturation, Brightness, Contrast and sharpness are adjustable by client software
Features	3D DNR, BLC, EIS, Defog, ROI
Network Storage	Micro SD/SDHC/SDXC card (up to 128G), NAS
Alarm Trigger	Tampering alarm, Network disconnect, IP address conflict, Storage full, storage error
Smart Features	Line Crossing Detection, Scene Change Detection Intrusion Detection, Audio Exception Detection Defocus Detection, Motion Detection, Face Detection Loitering, Rapid Motion Detection, Unattended Baggage/Object, Removal Detection, etc.
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP IGMP, 802.1X, QoS, IPv6, Bonjour
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Audio Interface	Audio in (Mic in / Line in) / output external interface
Communications	1 RJ45 10M/100M Ethernet Network
Housing Interface	1 anti-corrosion inlet protected by a metal hose
Video Output	1 Vp-p composite output (75 Ω/BNC)
Alarm	1 Input / output (up to DC24V or AC110V 500mA)
Operating Conditions	-40°C ~ +60°C, Humidity 95%
Power Supply	AC24V/DC12V/PoE(802.3at)
Power Consumption	16W MAX
IR Range	Approx. 10-30 m
Dimension	Φ165.4 × 126.2
Weight	3360g

Key Features

- Anti-corrosion stainless steel effectively avoid acidic and neutral salt fog corrosion
- 1920 x 1080 @ 25fps frame rate
- Ultra-low illumination
- True WDR, up to 120dB
- Smart Function, EIS, Defog
- PoE / 24VAC power supply
- IP66 weatherproof

Dimensions

